

TECHNICAL INFORMATION



Review 001 of 03/2010

Page 1 of 2


PRODUCT	
MARBLE CRYSTALLIZER – SH100	
FEATURES	
SH 100 grants a vitrified look, by removing the stone unstable molecules and restoring them with the compounds of its special formulation. The wax in it produces lasting final polish. Our SH 100 is appreciated for excellent reaction time and for remaining polished and unchanged in color even long time after application.	
TECHNICAL DATA	
Appearance	Liquid
Specific weight (MI 001)	1000 ± 20 g/l
Odor	Distinctive smell
Color	Dirty white – light brown
Packaging	
STORAGE	
Keep the packages well sealed and in suitable cool, well-ventilated environment for a maximum of 12 months from date of production printed on the tin.	
SAFETY NORMS	
Keep the place ventilated during application and drying processes. The use of personal protective equipment is recommended during application. Read carefully the safety data sheet before application.	
APPLICATION	
SH 100 is ready for use as supplied. - Clean carefully the surface to be treated and distribute the crystallizer SH 100 evenly over it, if possible use a sprayer. - Then use a monobrush (40 kgs. Approx.), preferably a 1,7 hp machine / 170 rpm, with fine steel wool disk. - It is recommended to treat small areas at a time, 4 m² maximum. - Spreading rate: from 20 to 40 m² depending on the type of material. Store the product at mild temperature in well-ventilated environment and do not expose it to heat sources.	

TECHNICAL INFORMATION

Review 001 of 03/2010

Page 2 of 2



APPLICATION		SPREADING RATE	
	Monobrush 170 g/min		20 – 40 m ² depending on material
ADDITIONAL INFORMATION			
Note: Since the <i>MARBLE CRYSTALLIZER – SH100</i> is formulated by mixing synthetic and natural waxes it could change color and odor, but this would not compromise application and ending result.			